



Insulation Certificate CCRR-0396

****DO NOT REMOVE THIS CERTIFICATE****
PLEASE POST NEAR ELECTRICAL PANEL

GENERAL INFORMATION

Project Address			
City	State:		ZIP Code:
Building Contractor			
Insulation Contractor			
Installed By	Phone #:		
Product Installed	Lot #:	<input style="width: 100px;" type="text"/>	<input style="width: 100px;" type="text"/>

Please consult International Building Code (IBC) Chapter 26 - Plastic and International Residential Code (IRC) R316 - Foam Plastics for specific requirements. The spray polyurethane foam insulation system(s) has/have been installed in accordance with manufacturer's processing guidelines to provide a thermal resistance of:

INSULATION OVERVIEW

Area Insulated	Aged R-Value	At	Thickness*	
Attic Area	R - <input style="width: 80px;" type="text"/>	At	<input style="width: 80px;" type="text"/>	inches
Sloped Ceilings	R - <input style="width: 80px;" type="text"/>	At	<input style="width: 80px;" type="text"/>	inches
Walls (location): <input style="width: 250px;" type="text"/>	R - <input style="width: 80px;" type="text"/>	At	<input style="width: 80px;" type="text"/>	inches
Walls (location): <input style="width: 250px;" type="text"/>	R - <input style="width: 80px;" type="text"/>	At	<input style="width: 80px;" type="text"/>	inches
Floors (over an unheated crawl space, garage, etc.)	R - <input style="width: 80px;" type="text"/>	At	<input style="width: 80px;" type="text"/>	inches
Crawl Space Perimeter	R - <input style="width: 80px;" type="text"/>	At	<input style="width: 80px;" type="text"/>	inches
Basement Walls	R - <input style="width: 80px;" type="text"/>	At	<input style="width: 80px;" type="text"/>	inches
Other (location): <input style="width: 250px;" type="text"/>	R - <input style="width: 80px;" type="text"/>	At	<input style="width: 80px;" type="text"/>	inches

* Nominal thicknesses are representative of field, spray-applied foam material

The foam plastic has been installed in accordance with the terms of CCRR-0396 and that any alterations to the attic must be consistent with those requirements. The attic or crawl space must be separated from the interior of the building by an approved 15-minute thermal barrier as described in CCRR-0396.

Area not intended for occupancy or storage. Occupied areas must be protected with a thermal barrier.

NOTE TO HOMEOWNER: Access to this attic is limited to servicing of utilities and equipment only, unless specifically designed for storage per building code requirements.

Signature:	Date:	Comments:
-------------------	--------------	------------------